



Model	Drive-train	Roll Diameter	Track Width	Adjustable Wheelbase	System Inertia	Peak Power	Absorbed Power	Max Speed
1200A-832	2WD	30" (76 cm)	26" inside - 100" outside (66 cm - 254 cm)	n/a	1,200 lb. (544 kg)	2,500 HP (1,864 kW)	1,100 HP (820 kW)	225 mph (362 km/h)
1200A-849	2WD	42" (107 cm)	28" inside - 96" outside (71cm - 243 cm)	n/a	2550 lb. (1157 kg)	2,500 HP (1,864 kW)	1,600 HP (1,193 kW)	200 mph (322 km/h)
1200A-832-AWD	AWD	30" (76 cm)	26" inside - 100" outside (66 cm - 254 cm)	92" - 130" (234 cm - 330 cm)	2,400 lb. (1,089 kg)	2,500 HP (1,864 kW)	850 HP (634 kW)	180 mph (290 km/h)
1200A-880E	AWD	42" (107 cm)	40" inside - 84" outside (101 cm - 213 cm)	88" - 134" (224 cm - 340 cm)	3467 lb. (1572 kg)	2,500 HP (1,864 kW)	1,600 HP (1,193 kW)	200 mph (322 km/h)
1200A-883	AWD	42" (107 cm)	Front: 40" inside - 84" outside Rear: 28" inside - 84" outside (Front: 101 cm - 213 cm Rear: 71 cm - 213 cm)	98" - 149" (249 cm - 378 cm)	3806 lb. (1726 kg)	2,500 HP (1,864 kW)	1,600 HP (1,193 kW)	200 mph (322 km/h)
1200A-888	AWD	42" (107 cm)	Front: 40" inside - 84" outside Rear: 40" inside - 96" outside (Front: 101 cm - 213 cm Rear: 101 cm - 243 cm)	98" - 149" (249 cm - 378 cm)	3886 lb. (1762 kg)	2,500 HP (1,864 kW)	1,600 HP (1,193 kW)	200 mph (322 km/h)
1200A-889	AWD	42" (107 cm)	28" inside - 96" outside (71cm - 243 cm)	98" - 149" (249 cm - 378 cm)	4925 lb. (2234 kg)	2,500 HP (1,864 kW)	1,600 HP (1,193 kW)	200 mph (322 km/h)



Phone : (021) 29563045 Fax : (021) 29563052
 Email : sales@testingindonesia.com Web : www.testingindonesia.com